

FHS2

Rubberized outer skin, anti-drop and durable





Single-mode/multi-mode light source
Single output port

Multiple wavelengths, stable output



850nm

1300nm

1310nm

1490nm

1550nm

Humanized design

With backlight LCD display function and low voltage automatic shutdown function.
Automatic shutdown after 10 minutes without operation







Positive



Negative



Side



Top



Bottom

Technical parameter

Items		Specifications				
		FHS2D02F	FHS2T01F	FHS2T02F	FHS2Q01F	FHS2Q02F
Output Power	-5dBm	√	√	√	√	√
Wavelength	1310/1550nm	√				
	1310/1490/1550nm		√			
	1310/1550/1625nm			√		
	850/1300/1310/1550nm				√	
	1310/1550/1490/1625nm					√
Others	270/1k/2kHz frequency	√	√	√	√	√
	Auto wavelength recognition	√	√	√	√	√

Laser type	LD
Power Supply	2*Ni-MH AA battery (Continuous use for 20 hours)
Working Temp	-10°C~+50°C
Storage Temp	-20°C~+70°C
Dimension/Weight	160L×76W×45H(mm) / 260g
Accessories	2*Ni-MH AA battery, FC adapter, SC adapter, 3*ceramic sleeves, Power adapter, USB cable, CD, Test report, Quick guide, Carrying bag
Customization	FC/APC, SC/APC, ST/APC